



802.11ac Wave-2 2x2:2 Wi-Fi Access Point

GWN7605

The GWN7605 is an affordable 802.11ac Wave-2 Wi-Fi access point ideal for small to medium wireless network deployments with medium user density. It offers dual-band 2x2:2 MU-MIMO with beam-forming technology and a sophisticated antenna design for maximum network throughput and expanded Wi-Fi coverage range. To ensure easy installation and management, the GWN7605 uses a controller-less distributed network management design in which the controller is embedded within the product's web user interface. The GWN7605 is also supported by GWN.Cloud and GWN Manager, Grandstream's cloud and on-premise Wi-Fi management platform. It is the ideal Wi-Fi AP for voice-over-Wi-Fi deployments and offers a seamless connection with Grandstream's Wi-Fi-capable IP phones. With support for advanced QoS, low-latency real-time applications, mesh networks, captive portals, 100+ concurrent clients per AP and dual Gigabit network ports with PoE/PoE+, the GWN7605 is a scalable Wi-Fi solution for deployments such as retail locations, restaurants, small offices and more.



1.27Gbps aggregate wireless throughput and 2xGigabit wireline ports



Supports 100+ concurrent Wi-Fi client devices



Dual-band 2x2:2 MU-MIMO with beamforming technology



Up to 165-meter coverage range



Self power adaptation upon auto detection of PoE/PoE+



Advanced QoS to ensure real-time performance of low-latency applications



Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device



Embedded controller can manage up to 50 local GWN series APs; GWN.Cloud offers unlimited AP management; GWN Manager offers premise-based software controller



Wi-Fi Standards	IEEE 802.11a/b/g/n/ac (Wave-2)
Antennas	2 dual band internal antennas 2.4GHz, gain 3dBi 5 GHz, gain 4dBi
Wi-Fi Data Rates	IEEE 802.11ac: 6.5 Mbps to 867 Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps; IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	*Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network
Frequency Bands	2.4 GHz Radio: 2412 – 2484 MHz 5 GHz Radio: 5180-5825 MHz
Channel Bandwidth	2.4G: 20 and 40 MHz 5G: 20,40 and 80 MHz
Wi-Fi and System Security	WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES), anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate and random default password per device
МІМО	2x2:2 2.4GHz (MIMO) 2x2:2 5GHz (MU-MIMO)
Coverage Range	Up to 165 meters *coverage range can vary based on environment
Maximum TX Power	2.4G:24dBm 5G:22dBm *Maximum power varies by country, frequency band and MCS rate
Receiver Sensitivity	2.4G 802.11b: -96dBm@1Mbps, -88dBm@11Mbps; 802.11g: -93dBm @6Mbps, -75dBm@54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz:-70dBm @MCS7 5G 802.11a: -92dBm @6Mbps, -74dBm @54Mbps; 802.11ac 20MHz: -67dBm@MCS8; 802.11ac: HT40:-63dBm @MCS9; 802.11ac 80MHz: -59dBm @MCS9
SSIDs	16 SSIDs total, 8 per radio (2.4 Ghz and 5 Ghz)
Concurrent Clients	100+
Network Interfaces	100+ 2 x autosensing 10/100/1000 Base-T Ethernet Ports
Network Interfaces	2 x autosensing 10/100/1000 Base-T Ethernet Ports
Network Interfaces Auxiliary Ports	2 x autosensing 10/100/1000 Base-T Ethernet Ports
Network Interfaces Auxiliary Ports Mounting	2 x autosensing 10/100/1000 Base-T Ethernet Ports 1 x Reset Pinhole, 1 x Kensington lock
Network Interfaces Auxiliary Ports Mounting LEDs	2 x autosensing 10/100/1000 Base-T Ethernet Ports 1 x Reset Pinhole, 1 x Kensington lock Indoor wall or ceiling mount, kits included
Network Interfaces Auxiliary Ports Mounting LEDs Network Protocols	2 x autosensing 10/100/1000 Base-T Ethernet Ports 1 x Reset Pinhole, 1 x Kensington lock Indoor wall or ceiling mount, kits included 3 x tri-color LED for device tracking and status indication
Network Interfaces Auxiliary Ports Mounting LEDs Network Protocols QoS	2 x autosensing 10/100/1000 Base-T Ethernet Ports 1 x Reset Pinhole, 1 x Kensington lock Indoor wall or ceiling mount, kits included 3 x tri-color LED for device tracking and status indication IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM
Network Interfaces Auxiliary Ports Mounting LEDs Network Protocols QoS	2 x autosensing 10/100/1000 Base-T Ethernet Ports 1 x Reset Pinhole, 1 x Kensington lock Indoor wall or ceiling mount, kits included 3 x tri-color LED for device tracking and status indication IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM 802.11e/WMM, VLAN, TOS Embedded controller can manage up to 50 local GWN APs GWN.Cloud offers a free cloud management platform for unlimited GWN APs
Network Interfaces Auxiliary Ports Mounting LEDs Network Protocols QoS Network Management Power and Green Energy Efficiency	2 x autosensing 10/100/1000 Base-T Ethernet Ports 1 x Reset Pinhole, 1 x Kensington lock Indoor wall or ceiling mount, kits included 3 x tri-color LED for device tracking and status indication IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM 802.11e/WMM, VLAN, TOS Embedded controller can manage up to 50 local GWN APs GWN.Cloud offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs PoE 802.3af/ 802.3at;
Network Interfaces Auxiliary Ports Mounting LEDs Network Protocols QoS Network Management Power and Green Energy Efficiency	2 x autosensing 10/100/1000 Base-T Ethernet Ports 1 x Reset Pinhole, 1 x Kensington lock Indoor wall or ceiling mount, kits included 3 x tri-color LED for device tracking and status indication IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM 802.11e/WMM, VLAN, TOS Embedded controller can manage up to 50 local GWN APs GWN.Cloud offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs POE 802.3af/ 802.3at; Maximum Power Consumption:10.16W Operation: 0°C to 40°C Storage: -10°C to 60°C
Network Interfaces Auxiliary Ports Mounting LEDs Network Protocols QoS Network Management Power and Green Energy Efficiency Environmental Physical	2 x autosensing 10/100/1000 Base-T Ethernet Ports 1 x Reset Pinhole, 1 x Kensington lock Indoor wall or ceiling mount, kits included 3 x tri-color LED for device tracking and status indication IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM 802.11e/WMM, VLAN, TOS Embedded controller can manage up to 50 local GWN APs GWN.Cloud offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs PoE 802.3af/ 802.3at; Maximum Power Consumption:10.16W Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing Unit Dimension: 180.4mmx180.4mmx40.8mm; Unit Weight: 388.2g
Network Interfaces Auxiliary Ports Mounting LEDs Network Protocols QoS Network Management Power and Green Energy Efficiency Environmental Physical Package Content	2 x autosensing 10/100/1000 Base-T Ethernet Ports 1 x Reset Pinhole, 1 x Kensington lock Indoor wall or ceiling mount, kits included 3 x tri-color LED for device tracking and status indication IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM 802.11e/WMM, VLAN, TOS Embedded controller can manage up to 50 local GWN APs GWN.Cloud offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs POE 802.3af/ 802.3at; Maximum Power Consumption:10.16W Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing Unit Dimension: 180.4mmx180.4mmx40.8mm; Unit Weight: 388.2g Entire Package Dimension: 228.5x220x79mm; Entire Package Weight: 719.3g

